


# **MOLYSLIP MLG**

(Moly E.P. Lithium Grease)



### **GENERAL DESCRIPTION:**

MOLYSLIP MLG is a Multi-purpose Moly EP lithium grease. Formulated for extreme pressure load bearing capacity and resistance to oxidation and corrosion. It helps to prolong periods between maintenance and routine greasing.

#### PERFORMANCE AND APPLICATIONS:

 $\label{thm:linear_problem} \mbox{HIGH PERFORMANCE GREASE-Lithium based with Molybdenum Disulphide, extreme pressure and anti-corrosion additives.}$ 

EXTREME PRESSURE LOAD CAPACITY – Formulated to provide exceptionally high load bearing capacity enabling prolonged maintenance and routine greasing intervals.

HIGH OXIDATION STABILITY – Provides rust prevention and minimises fretting corrosion. Good resistance against fresh or salt water contamination.

### **APPLICATIONS INCLUDE:**

- For all ball and roller bearings where grease lubrication is specified, particularly medium to high speeds.
- · General chassis and machinery lubrication.
- · Hub and electric motor grease lubricated bearings.
- Plain bearings, slides, screws and valve threads for dockside, dock equipment, general transport
  and industrial applications.
- All types of applications to sustain heavy duty or prolong life of components and to reduce friction and wear.

## **TECHNICAL DATA:**

Base	Lithium	
Consistency	N.L.G.I. No.2	
Worked penetration at 25°c	265 - 295	
Melting Point	195°C	
Total MoS2 and Molyslip Special E.P. compounds	9%	
Steady Working Temperature	-30°C to  50°C	

## **PACKAGING:**

450g tins (carton of 24) 400g cartridges (carton of 24) 5kg tins (carton of 2 or 4) 12.5kg, 25kg, 50kg and 180kg (individual)

01 October 2012